



## CHOICE OF PARAMETERS FOR COMBINED RENEWABLE ENERGY INSTALLATIONS

Olimov O.N.,  
Narimanov B.A.,  
Suyarov A.O.,  
Sorimsokov U.S.

Assistant Teacher, Jizzakh Polytechnic Institute, Department of "Energy"

### ANNOTATION:

The calculation of the economic characteristics of RES installations with known TE characteristics can be carried out in the usual ways. However, the variability of RES and, in connection with this, the variability of energy characteristics requires that these features of RES be taken into account in the calculations

**Keywords:** RES power plants, "compositional" method, power supply of the station, the main parameters of the CPP (helio+wind), the main parameters of the MED.

### Introduction

One of the main tasks in the field of using RES power plants is to ensure their economic feasibility. To solve this problem, it is necessary to know the relationship between the technical and economic parameters and indicators of renewable energy installations, which is significantly more complicated given the variability of renewable energy sources over time and, in connection with this, the difficulties of coordinating the modes of energy generation and consumption, as well as, as a rule, the need for renewable energy installations to store energy (AB). To determine the economic characteristics.

In general, the calculation of the economic characteristics of RES installations with known TE characteristics can be carried out in the usual ways. However, the variability of RES and, in connection with this, the variability of energy characteristics requires that these features of RES be taken into account in the calculations.

In /10/, on the example of a combined wind turbine and a solar plant, the feature of calculating the t-e of RES installations was first considered. The proposed "compositional" method was based on the consideration of the structure of real fluctuations in the productivity of wind turbines QB and solar power plants QE, as separate dissected components of the process Q under study. and the random nature of the receipt of RES. The main conclusion from the analysis of the methodology is that studies of renewable energy sources by the compositional method for the water





management and energy use of these sources should be carried out for all months for 15-20 years in order to predict sufficiently reliable statistical patterns. In general, it can be noted that the average data on RES (wind and Sun) as a whole are obviously constant, especially for months and seasons, but it is also obvious that for a particular day there will be quite large discrepancies between the average and real values of RES receipts.

On the basis of the developed methodology, the author /10/ conducted a generalized study of the CES for the cases of water supply to the pastures of the Kyzylkum desert, power supply of the station of radio relay lines (RRL) along the Bukhara-Ural highway with a branch in Nukus, as well as for the Gazalkent-Charvak recreation area /11 /. The calculations were carried out in order to determine the volume of the water accumulator (A) at various values of the consumer's supply. It is shown that at 90% supply, the volume A of water, as well as electric AB at 98% supply of RRL energy, when using CPP, is 3 times less in summer and 5.5 times less in autumn than when SPP and WPP are used separately. It is indicated that the final choice of CEU parameters should be made by comparing the installation options. However, what are the costs of the CES and its components were not considered.

Methods. In /12/ a mathematical model for calculating and optimizing the main parameters of the CPP (helio+wind) was proposed. The basic equation of the model is the total reduced costs for the construction and operation of the power plant, taking into account the profit and damage from the production of products. The main conclusion obtained in the work is that, depending on the potential of renewable energy sources in a particular area, it may be beneficial not for CPPs, but for individual wind turbines or power plants.

Results. The comments on the work include the following:

- The model is quite generalized, so the model has technical and economic characteristics (empirical dependencies of cost on power are presented), but the dependencies of power change and efficiency are not taken into account. power plants from RES parameters. Those. in the KEU model, it is necessary to separately identify and set the technical and economic characteristics of the KEU and, in general, the relationship between them.
- the initial data are not selected in the model - what load should the power plant provide.
- it is important to note that in the work, their long-term average values were used as initial data for wind and solar energy, i.e. in the estimates, these indicators were seasonal variables, and for shorter periods of a day, a week, a month, their actual constant values were used.





In /13/ the cost of wind-solar power plants was estimated for the case of a constant load relative to the average solar radiation during the day and a constant wind speed. In /14/ on the basis of the model developed in /13/, the energy cost of such a CPP was estimated. It was found that the share of the solar part at constant load and constant power generation by the wind part is significantly small and does not exceed 5%. It was also concluded that the cost of CPP as a whole is higher than individual installations of wind turbines and SFEU, which is not consistent with the conclusions of Makhkamdzhanov B.M.

In /25/ estimates of the cost of electricity are given for the estimated generation of wind power plants with a capacity of 60, 250 and 500 kW, mass-produced by Taske (Germany) in the region of 88 meteorological stations in Uzbekistan. Based on the analysis, areas were identified where the expected cost of generated energy is at the level of world achievements; the most suitable types of wind turbines for wind conditions in these areas and effective ways of their application are determined. However, the cost of wind turbine power for the consumer is not given for the available wind speed ranges, which differ significantly from the nominal nameplate wind speeds for wind turbines.

In /26/ the justification and development of a technological model of a multi-purpose water-energy complex with the combined use of solar, wind, and microhydroelectric power was proposed. The proposed technological scheme is the combined use of solar, wind, water energy in the generation of electricity, which is used for domestic needs (lighting, radio equipment, etc.) and the production and technological needs of livestock farms: water supply, water quality improvement, power supply. The work is aimed at improving the efficiency of using the existing wind turbine, this is true, but the issues of optimizing the CPP itself were not considered.

In /27/, a description of the technological scheme of a model of an autonomous installation operating on renewable energy sources for generating electricity and drinking water was proposed, and a study of its operational capabilities. It is shown that the above analysis, the advantage of the proposed scheme of the wind-solar complex lies in the fact that during the normal operation of its modules it is possible to accumulate the produced product in order to ensure the generation of electricity for the consumer using FC under adverse weather conditions for the operation of the complex.

In /28/, it was proposed to identify and evaluate the possibilities of using the energy of the sun, wind and small rivers to provide heat supply and improve the power supply of non-gasified SNPs in the above zone. The predicted consumption of electrical and thermal energy of residential buildings in rural settlements in the mountainous





Chimgan-Charvak zone, including those not subject to gasification until 2010, was determined. The possibilities of covering these loads with the help of solar photovoltaic installations were considered; wind power plants of small and medium capacity in areas for which the observational data at the MS Charvak reservoir are representative; small hydroelectric power stations on the river. Pskem, Ugam and Chingansay. The paper considers the possible potentials of renewable energy sources, however, an economic assessment of the use of these renewable energy sources has not been carried out.

In /29/ the main principles of the combined use of RES were presented, as well as ways to increase the efficiency of the energy complex based on solar, wind and hydraulic energy by accumulating their generation. Based on the selected methods and accumulated information, as well as the results of calculations, the most effective option for building an energy complex is selected. The model does not consider such points as the criteria for optimizing the CPP, the relationship of the output characteristics of the CPP depending on the supply of RES.

In /30/ the issues of designing an autonomous source of electricity with renewable energy converters were considered. The structural-technological scheme of the combined power source, mathematical models for calculating the capacity of the storage device and the energy balance are given. On the basis of mathematical modeling of the output energy parameters of the power source, a block diagram of the algorithmization of designing a combined power source with solar-wind energy converters together with a low-power hydraulic unit has been developed. It can be noted that, as in /30/, it is precisely the features of RES that are not considered - the variability of the supply and, accordingly, the variability of the output power, as well as the criteria for optimizing the parameters of the CPP.

In /31/ indicators of the cost of power and mass of microhydroelectric power plants were considered by analogy with the density of solar radiation, depending on the density of the energy flow of water. The dependences of the change in these indicators with a change in the energy of the water flow are determined.

In /32/ options for using a microhydropower plant were considered, generalized models of its technological process were built, and a method for determining the main parameters of this plant was also described. It is said that on the basis of the proposed methodology, the main parameters of the MED and the required amount of accumulated energy at the design stages can be determined.

In /33/ the questions of combined use of micropower installations with hydrostorage and without it were considered, as well as the characteristics of the economic efficiency of their work, depending on the load schedule of consumers.



## Discussion

The following conclusions are obtained:

1. With sufficient wind energy potential, it is recommended to use MPP based on wind turbines and power plants with accumulation of excess wind energy in the upper basin.
2. In conditions of insufficient return of wind energy, in order to improve the reliability of power supply, it is advisable to use controlled MPPs based on wind turbines, SPPs and GPPs with a hydraulic accumulator.
3. The use of a hydraulic accumulator in combined systems for the use of renewable energy sources leads to a reduction in annual costs and the cost of energy compared to the option without a hydraulic accumulator.

However, all these conclusions were obtained for the case of constant load and constant power of RES, i.e. variability of RES and output characteristics of CPP was not taken into account.

## REFERENCE

1. Клычев Ш.И., Мухаммадиев М.М., Авезов Р.Р., Потаенко К.Д. Нетрадиционные и возобновляемые источники энергии. Учебник –Т.: Изд-во “Fan va texnologiya”, 2010, 192 стр.
2. Клычев Ш.И., Исманжанов А.И Солнечные сушильные установки и комплексы: расчет и проектирование/Ин-т природных ресурсов НАН КР. – Бишкек: Илим. 2011. -132 с.
3. Мухаммадиев М.М. и Потаенко К.Д. Возобновляемые источники энергии. Учеб.пособ., ТашГТУ, 2005.
4. Джуманов А. Н. и др. Измерительные трансформаторы тока //World science: problems and innovations. – 2021. – С. 76-78.
5. Mamasaliev O. Theoretical Foundations of Energy Saving //International Journal of Engineering and Information Systems (IJEAIS) ISSN. – 2021. – С. 293-296.
6. Suyarov A. O. et al. Use of solar and wind energy sources in autonomous networks //Web of Scientist: International Scientific Research Journal. – 2022. – Т. 3. – №. 5. – С. 219-225.
7. Sorimsokov U. Use of alternative energy to reduce power losses and improve voltage //Gospodarka i Innowacje. – 2022. – Т. 23. – С. 20-25.
8. Mamasaliev O., Sarimsoqov U. Calculation of wires for mechanical strength //Студенческий вестник. – 2021. – №. 21-10. – С. 15-19.
9. Olimov O. Basic Ways to Improve Efficiency Operations of Asynchronous Electric Drives //International Journal of Engineering and Information Systems (IJEAIS)





ISSN. – 2020. – С. 107-108.

10. Suyarov A. O. et al. Renewable energy research in uzbekistan: prospects and challenges //Web of Scientist: International Scientific Research Journal. – 2022. – Т. 3. – №. 5. – С. 1490-1498.
11. Suyarov A. O. et al. Use of solar and wind energy sources in autonomous networks //Web of Scientist: International Scientific Research Journal. – 2022. – Т. 3. – №. 5. – С. 219-225.
12. Suyarova, M. X. (2019). Teaching physics in a technical university. Экономика и социум, (12), 123-125.
13. Иняминов, Ю. А., & Суярова, М. Х. (2021). Принципы построения индивидуальных радиоприёмных устройств спутникового телевидения. Science and Education, 2(11), 342-349.
14. KHUSANOVNA, S. M., & GULNOZAALIEVNA, A. ADVANTAGES AND DISADVANTAGES OF USING MULTIMEDIA IN TEACHING FOREIGN LANGUAGES. XORIJIY TILLARNI O „QITISHNING DOLZARB MASALALARI: MUAMMOLAR VA YECHIMLAR, 170.
15. Суярова, М. Х. (2021). УСПЕШНОЕ РАЗВИТИЕ И ЭФФЕКТИВНОЕ ФУНКЦИОНИРОВАНИЕ ТЕЛЕКОММУНИКАЦИОННЫХ СИСТЕМ РЕСПУБЛИКИ УЗБЕКИСТАН. In НАУКА, ОБРАЗОВАНИЕ, ИННОВАЦИИ: АКТУАЛЬНЫЕ ВОПРОСЫ И СОВРЕМЕННЫЕ АСПЕКТЫ (pp. 67-69).
16. Суярова, М. Х., & Мустафакулов, А. А. ТВОРЧЕСКИЕ ЗАДАЧИ ПО ЭЛЕКТРОМЕХАНИКЕ. «ИННОВАЦИОН ИҚТИСОДИЁТ: МУАММО, ТАҲЛИЛ ВА РИВОЖЛАНИШ ИСТИҚБОЛЛАРИ» Халқаро илмий-амалий анжуман илмий мақолалар тўплами 20-21 май 2021 й., 418.
17. Суярова, М. Х., & Джураева, Н. М. (2018). Динамическая модель по электротехнике. In Передовые научно-технические и социально-гуманитарные проекты в современной науке (pp. 53-54).

